


VX-8R APRS SETUP

Enter APRS Set Mode

MENU  **MENU** **24 TIME ZONE**
1 APR AF DUAL
2 APRS DESTINATION
3 APRS FILTER

1/2 SEC 1 SEC

Time Zone (Set Mode Item 24)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **DIAL** **PTT**
MENU 1 SEC

SET MODE #24 ENABLE SET TIME ZONE CONFIRM

My Callsign (Set Mode Item 20)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **SPS SQ TYP** **MODE** **DIAL** **MENU**
MENU 1 SEC

SET MODE #20 ENABLE CURSOR→ "CHAR" SAVE

My Symbol (Set Mode Item 22)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **DIAL** **MENU**
MENU 1 SEC

SET MODE #22 ENABLE "ICON" SAVE

Position Comment (Set Mode Item 23)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **DIAL** **MENU**
MENU 1 SEC

SET MODE #23 ENABLE "COMMENT" SAVE

VX-8R APRS SETUP (continued)

My Position (Set Mode Item 21)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **DIAL** **MENU**
MENU 1 SEC

SET MODE #21 ENABLE "AUTO" SAVE

ARPS Modem (Set Mode Item 4)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **DIAL** **MENU**
MENU 1 SEC

SET MODE #4 ENABLE "1200BPS" SAVE

Digipeater Path (Set Mode Item 15)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **DIAL**
MENU 1 SEC

SET MODE #15 ENABLE "PATH NUMBER"

Digipeater Path Continued

SPS SQ TYP **MODE** **DIAL** **SPS SQ TYP** **MODE** **PTT**

CALLSIGN ENTRY "CHARS" CURSOR→ SAVE

Created and Maintained By

VX8R@GEARMONKIES.COM
PLEASE SEND ALL COMMENTS AND/OR CORRECTIONS
TO THE ABOVE EMAIL ADDRESS. THANK YOU.

VX-8R APRS GEAR MONKIES GUIDE - VERSION .1(FEEDBACK)

VX-8R APRS OPERATION

Tune APRS Frequency

B  **DIAL**

SET B BAND TUNE VFO SET APRS FREQUENCY

Disable RX Battery Saver (Set Mode Item 79)

MENU **DIAL** **MENU** **DIAL** **MENU**

1/2 SEC #79 ENABLE SET SAVE RX CONFIRM

Manual Transmit APRS Beacon

B **TX PO** 

SET B BAND PRESS TO TX BEACON

AutoTransmit APRS Beacon (set Mode Item 14)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **DIAL** **MENU**
MENU 1 SEC

SET MODE #14 ENABLE "AUTO" SAVE

Beacon Interval (Set Mode Item 12)

ENTER APRS
MENU 1/2 SEC **DIAL** **MENU** **DIAL** **PTT**
MENU 1 SEC

SET MODE #12 ENABLE "INTERVAL" SAVE